



Technical Data



	Standard	Result	Product	Size (mm)	Slip Resistance Oil-Wet Ramp																		
Size	ISO 24342	See separate table	AP01	228 X 76	R9																		
Thickness	ISO 24346	3.0 mm	AP02	228 X 76	R9																		
Wear Layer		0.7 mm	AP03	228 X 76	R9																		
Surface treatment		K-Guard+ PU coating	EW01	915 X 152	R9																		
Warranty	Commercial	20 years wear*	EW02	915 X 152	R9																		
	Domestic	Lifetime wear*	EW03	915 X 152	R9																		
Bevelled Edge		Yes	HC01	915 X 152	R9																		
Standards	EN 649/EN ISO 10582	Pass	HC02	915 X 152	R9																		
	ASTM F1700	Pass	HC03	915 X 152	R9																		
Classification		Commercial Very Heavy Duty use	HC04	915 X 152	R9																		
		Domestic Extra Heavy Duty use	HC05	915 X 152	R9																		
Staining Resistance	EN 423	Class 0	HC06	915 X 152	R9																		
	ASTM F925	Pass	LM01	915 X 915	R10																		
Colour Fastness to Light	ISO 105-B02	≥6	LM03	915 X 915	R10																		
	ASTM F1515	<8	LM05	610 X 457	R10																		
Abrasion Resistance	EN 660-2	Group T	LM06	610 X 457	R10																		
	ISO 10582	Type 1	LM07	610 X 457	R10																		
	ASTM D3884	Pass	LM08	610 X 457	R10																		
Flexibility	ISO 24344	Pass	LM09	610 X 457	R10																		
Dimensional stability	EN 434/ISO 23999	≤ 0.25%	LM15	406 X 406	R9																		
	ASTM F2199	Pass	LM16	406 X 406	R9																		
Acoustic Impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 2 dB**	LM17	Free Length X 152	R10																		
Electrical behaviour body voltage	EN 1815	Pass	LM18	Free Length X 152	R10																		
Indentation - residual	EN 433/ ISO 24343-1	≤ 0.1mm	LM19	Free Length X 152	R10																		
	ASTM F1914	<8%	LM21	610 X 457	R10																		
Castor chair continuous use	EN 425/ ISO 4918	Pass	LM22	610 X 457	R10																		
Thermal resistance	ISO 8302	0.0147 m ² K/W	RL01	1219 X 178	R9																		
		Suitable for underfloor heating	RL02	1219 X 178	R9																		
Reaction to Fire	AS/NZS 9239.1:2003	<table border="1"> <thead> <tr> <th></th> <th>CRF:</th> <th>Smoke value:</th> </tr> </thead> <tbody> <tr> <td>Art Select Stone</td> <td>8.8 kW/m²</td> <td>151% min</td> </tr> <tr> <td>Hand Crafted Wood</td> <td>7.1 kW/m²</td> <td>121% min</td> </tr> <tr> <td>Oak Royale</td> <td>6.4 kW/m²</td> <td>114% min</td> </tr> <tr> <td>Oak Premier</td> <td>8.5 kW/m²</td> <td>177% min</td> </tr> <tr> <td>Parquet</td> <td>8.5 kW/m²</td> <td>220% min</td> </tr> </tbody> </table>		CRF:	Smoke value:	Art Select Stone	8.8 kW/m ²	151% min	Hand Crafted Wood	7.1 kW/m ²	121% min	Oak Royale	6.4 kW/m ²	114% min	Oak Premier	8.5 kW/m ²	177% min	Parquet	8.5 kW/m ²	220% min	RL03	1219 X 178	R9
	CRF:	Smoke value:																					
Art Select Stone	8.8 kW/m ²	151% min																					
Hand Crafted Wood	7.1 kW/m ²	121% min																					
Oak Royale	6.4 kW/m ²	114% min																					
Oak Premier	8.5 kW/m ²	177% min																					
Parquet	8.5 kW/m ²	220% min																					
			RL04	1219 X 178	R9																		
***Slip resistance	AS/NZS 4586:2013	See separate table																					
Adhesive	General use:	Karndean Mega-Bond																					
	High temperature:	Karndean 8000 2-part Polyurethane																					
Recycling		Suitable																					
Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level'A'; LCA Silver Plus; Best Practice PVC																					
Phthalate free		Yes																					

*Subject to terms

**Result is Ln,w = 58 dB when installed on Regupol 4515 acoustic underlay

***Slip resistance is measured on ex-factory product. Slip resistance in use will be affected by surface contamination and by how the product is maintained

For more information:

Australia

Call: 1800 33 11 70

Email: customerservice@karndean.com.au

Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01

Email: customerservice@karndean.co.nz

Visit: www.karndean.com

Manufactured to ISO9001

