

Designated Building Product: **Class 1**

Version 2.0 July 2025

Declaration

Belgotex New Zealand Ltd (Belgotex NZ) has provided this declaration to satisfy the provisions of the [Building Product Information Requirements \(BPIR\) Regulations 2022](#).

Company Details

Name	Belgotex New Zealand Limited
Role	Supplier
NZBN	9429038353000
Address	25 Leslie Hills Drive, Riccarton, Christchurch 8011
Website	www.belgotex.co.nz
Email	info@belgotex.co.nz
Phone	0800-377-753

Description of Building Product

Belgotex NZ supplies a range of [Commercial Heterogeneous Sheet Vinyl flooring](#) for installation and use in commercial or industrial environments.

Commercial Heterogeneous Sheet Vinyl flooring is a resilient flooring made from Polyvinyl Chloride (PVC) resin and consists of multiple layers—such as a protective wear layer, printed design layer, core layer, and backing—bonded together using high heat and pressure to form a durable, multi-material structure. The flooring is supplied as wide rolls for wall-to-wall installation.

Commercial Heterogeneous Sheet Vinyl flooring is supplied in full rolls measuring 2.0m, 3.0m, or 4.0m in width. Partial rolls are also available on request.

Belgotex NZ supplies accessories—weld rod, clean corner, ramping, coving, and edging—that are integral to the installation system and are covered under this declaration.

When installed, Commercial Heterogeneous Sheet Vinyl flooring may contribute to G6 (Airborne and impact sound). Compliance with this requirement needs to be established as part of the proposed flooring system.

Building Code Obligations

When installed in accordance with Belgotex NZ installation requirements, Commercial Heterogeneous Sheet Vinyl flooring may contribute to compliance with the applicable performance criteria under the following Building Code clauses.

Building Code Clause	Contribution to Compliance
B2 (Durability) B2.3.1(c)	Durability under commercial or industrial use has been established through evaluation to EN 14041.

	Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring has been reliably supplied and installed in buildings in New Zealand for over 15 years, demonstrating a strong track record of in-service performance.
C3 (Fire affecting areas beyond the fire source) C3.4(b)	Critical Radiant Flux (CRF) values exceeding 4.5 kW/m ² have been determined through testing to ISO 9239-1:2010. Refer to the Commercial Heterogeneous Sheet Vinyl range statement for specific CRF values. Commercial Heterogeneous Sheet Vinyl flooring can be used in all building areas and all risk groups.
D1 (Access routes) D1.3.3 (d)	Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring provides acceptable slip resistance for level access routes, slopes, and stairs expected to remain dry under normal use as per D1/AS1 Table 2. Certain products meet Slip Resistance Value, SRV ≥39 (AS 4586 Appendix A) or R11 rating (AS 4586 Appendix D), making them acceptable for use in level access routes expected to be wet in normal use. Refer to the range statement for specific SRVs or slip resistance ratings. Gerflor Tarasafe H2O and Tarasafe Ultra H2O meet barefoot slip resistance ratings B and C respectively, according to AS 4586 Appendix C, making them acceptable for use around swimming pools and adjacent to communal showers. An alternative solution can be supported by results of oil-wet ramp slip resistance testing to DIN 51130.
E3 (Internal moisture) E3.3.3 E3.3.5 E3.3.6	Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring qualifies as an integrally waterproof sheet material in accordance with E3/AS1 3.1.1(a). When sealed or coved at areas subject to water splashes, it meets the requirement for impervious and easily cleanable surfaces.
F2 (Hazardous building materials) F2.3.1	Low emission of volatile organic compounds (VOCs) has been established through assessment and certification to FloorScore or Émissions Dans L'air Intérieur A+ standard.

Scope of use and Limitations

Scope	Limitation
For all building classified uses	<ul style="list-style-type: none">Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring is for interior use only.Concrete substrate must have a relative humidity of 75% or below.Seams must be welded with weld rod supplied by Belgotex NZ.Flooring must be laid using adhesive specified by Belgotex NZ.Flooring must be laid in accordance with Belgotex NZ Installation Instructions.
For use in wet areas (bathrooms, toilets, laundries, kitchens)	<ul style="list-style-type: none">When installed in wet areas, Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring must be edge sealed as detailed in Belgotex NZ Installation Guidelines.Seams must be welded where required as per FloorNZ Best Practice Guidelines.

For use in access routes	<ul style="list-style-type: none">Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring is suitable for use in access routes.
In connection with underfloor heating including in-slab piped water heating.	<ul style="list-style-type: none">Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring is suitable for use with underfloor heating not exceeding 27°C.

Conditions of use

Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring must be installed according to Industry [Best Practice Guidelines](#) published by FloorNZ and maintained according to Belgotex NZ Care & Maintenance Guidelines available at www.belgotex.co.nz.

Additional Information

For all specification, installation, maintenance and warranty information, and all information supporting Belgotex NZ claims, refer to www.belgotex.co.nz.

Responsible Person

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore, to the best of my knowledge, correct.

I can also confirm Belgotex NZ Commercial Heterogeneous Sheet Vinyl flooring, as referred to in this statement, is not subject to a warning or ban issued under [Section 26 of the Building Act](#).

Signed for and on behalf of Belgotex New Zealand Limited

Jeremy Parish

Managing Director

24/07/2025