



DIMENSIONS

Length	165mm
Width	131mm
Thickness	8mm
Bevels	Genuine Bevel 4 sides
Number of panels per pack	14
m ² per pack	1.201m ²
Joining system	Unizip
Water damage warranty	15-year waterproof surface

FACTORY WARRANTY

	METHOD	PARAMETERS	NORM REQUIREMENTS	QUICK-STEP VALUES
Usage class	EN 13329			Class 32
Warranty	Residential use	See warranty conditions	See warranty conditions	Lifetime (33-year) Wear warranty
	Commercial use	See warranty conditions	See warranty conditions	15-year Waterproof Surface
				Wear warranty on Application

GENERAL DATA

	METHOD	PARAMETERS	NORM REQUIREMENTS	QUICK-STEP VALUES
Wear resistance	EN 13329		>4,000 cycles	With overlay Class 32
Wear class	EN 13329		AC4	With overlay AC4
Impact resistance	EN 13329		IC2	IC2
Scratch resistance	EN 438-2:25		Charge ≥ 3N	Charge ≥ 5N
Effect of a castor chair	ISO 4918 (with underlay)	Type W (EN 12529)	25,000 cycles	No change
Thickness swelling	ISO 24336	After 24hr immersion at 20°C	≤ 18%	≤ 12%
Locking strength	ISO 24334	F10.2 long side	≥ 1 kN/m	≥ 1 kN/m
		Fmax long side		≥ 1 kN/m
		Fs0.2 short side	≥ 2 kN/m	≥ 2 kN/m
		Fmax short side		≥ 2 kN/m
Effect of furniture leg	EN 424		No damage shall be visible, when tested with foot type 0	No visible Damage
Surface soundness	EN 13329	N/mm ²	≥ 1.25	≥ 1.50
Static indentation	EN 24343	Residual indentation	≤ 0.05mm	No visible change
Resistance to staining	EN 438	Group 1, 2	Class 5	Class 5
		Group 3	Class 4	Class 5
General appearance	EN 13329	Height difference	≤ 0.15mm	≤ 0.15mm
		Opening between joints	≤ 0.20mm	≤ 0.20mm
		Cupping in the length	concave ≤ 0.50%	≤ 0.50%
			convex ≤ 1.0%	≤ 1.0%
Cupping in the width	concave ≤ 0.15%	≤ 0.15%		
	convex ≤ 0.20%	≤ 0.20%		
Dimensional variations after changes in relative humidity	EN 13329	δl	δl average ≤ 0.9mm	≤ 0.9mm
		δw	δw average ≤ 0.9mm	≤ 0.9mm
Light fastness	EN ISO 4892-2:2013 procedure B – cycle 2 or cycle 5	Grey reference	Class ≥ 4	Class ≥ 4





OTHER TECHNICAL, ENVIRONMENT, SAFETY & HEALTH DATA

	METHOD	PARAMETERS	NORM REQUIREMENTS	QUICK-STEP VALUES
Formaldehyde emission	EN 717-1	ppm (large chamber)		< E0.5
Anti-static	EN 1815		≤ 2.0 kV	≤ 2.0 kV
Reaction to fire	AS/ISO 9239.1	Class		6.7kW/m ² /Smoke 7%
Thermal resistance	EN 12667	m ² K/W		0.055m ² K/W
Floor heating		On Quick-Step underlay	See special installation instructions	Suitable
Slip resistance	AS 4586	Pendulum test		P5

CERTIFICATES

EU Ecolabel	SE/035/001
AFFSET	A+
PEFC	PEFC/07-32-37
M1	
Nordic Ecolabel	30290001
EPD	

