

# Maiden Lane

44oz

<b>Construction:</b>	Tufted Cut Pile Carpet
<b>Yarn:</b>	100% Solution Dyed Nylon (SDN)
<b>Width:</b>	3.66m Broadloom
<b>Standard Roll Length:</b>	35m
<b>Yarn Weight:</b>	1492g/m <sup>2</sup> / 44oz/yd <sup>2</sup>
<b>Pile Height:</b>	9.0mm
<b>Total Thickness:</b>	11.0mm
<b>Machine Gauge:</b>	1/8th
<b>Primary Backing:</b>	Woven Polypropylene
<b>Secondary Backing:</b>	Action Fleece
<b>Electrical Properties:</b>	Antistatic
<b>Electrical Propensity:</b>	0.2kV (ISO 6356)
<b>Anti-Allergenic Properties:</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Underfloor Heating:</b>	Suitable
<b>Rating:</b>	Extra Heavy Duty Residential / Light Duty Commercial
<b>Stair Rating:</b>	Suitable
<b>Warranties:</b>	10 Year General Warranty 10 Year Residential Wear Warranty 10 Year Stain Resistant Warranty 10 Year Fade Resistant Warranty 10 Year Colourfast Warranty 3 Year Manufacturing Defects Warranty 3 Year Commercial Wear Warranty
<b>Environmental:</b>	Low VOC, solution dyeing uses no water CRI Green Label Certified ISO 14001
<b>Installation:</b>	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted.  All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.