

Apollo 1500



105
Thredbo



175
Franklin



515
Pyrenees



525
Alpine Gum



535
Derwent



545
Blackbutt



551
Daintree




556
Spotted Gum



571
Sherbrooke



721
Cumberland



730
Boston



790
Midnight

Apollo 1500

Apollo 1500 is a stunning hybrid floor that is extremely hard wearing and stable with a waterproof surface[^], making it perfect for use in all areas of your home. With micro bevel edges and an embossed matte finish, Apollo 1500 authentically replicates a natural timber wood grain look. A scratch and stain resistant surface coating means Apollo 1500 can easily withstand the everyday wear and tear of busy family homes.

Technical Data

Type:	Hybrid Flooring	Finish:	Matte
Dimensions:	1500mm x 180mm	Surface:	Embossed
Total Product Thickness:	6.5mm	Top Layer:	Decorative Film & Wear Layer
Wear Layer:	0.5mm	Substrate Layer:	Trigon® Core Technology (Limestone Composite)
Units Per Box:	6 boards	Backing Layer:	1.5mm Acoustic Backing
m² per box:	1.62	Profile:	Micro Bevel
m² per pallet:	113.4	Coating System:	PUR & Scratch Resistance
Colours:	12	Installation Method:	Uniclic®

Performance

Dimensional Stability:	(ISO 23999) Length: 0.05%, Width: -0.00%, Curling: 0.00%	Light Reflectance Values:	Available on Request
Abrasion Rating:	(EN 660-2) Group T	Flammability:	(EN ISO 9239) CRF 10.9kW/m ²
E3 Internal Moisture:	3.0 Watersplash - Alternative solution	Smoke Value:	(EN ISO 9239) 81% minutes
Impact Sound Reduction:	Please refer to Godfrey Hirst Acoustic Performance specification sheet	Slip Resistance:	(AS/NZ 4586-2013) P3
Light Fastness:	(EN ISO 105-B02) Grade 6		

Sustainability

Product Transparency:	Global Green Tag, GreenRate Level A certified
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits



Embossed



Mid Range



Waterproof Surface[^]



ISO 9001 Quality Management System



Global Green Tag



Uniclic®



ISO 14001 Environment Management System




0.5mm Wear Layer



Colour Variation



Matte Finish



Micro Bevel Edge