



Construction	Heterogeneous Sheet Vinyl
Width	2.0m
Standard Roll Length	25m
Total Weight	2949g/m ²
Wearlayer Thickness	0.7mm
Total Thickness	2.0mm
Surface Protection	Hyperguard+®
Slip Resistance	R10 (AS 4586:2013)
Electrical Properties	Antistatic
Electrical Propensity	≤ 2kV (EN 1815)
Fire Rating	Bfl-S1 (EN ISO 9239-1: 2010)
Acoustic Insulation	ΔLw 7dB (ISO 717-1)
Dimensional Stability	≤0.04% (EN ISO 23999)
Thermal Insulation	0.25W/m/K (EN 12524)
Underfloor Heating	Suitable
Colour Fastness	6 (ISO 105B02)
Chemical Resistance	Very Good (EN ISO26987)
Abrasion Resistance	Group T (EN 660-2)
Classifications	Class 23 Domestic Heavy / Class 34 Commercial Very Heavy / Class 43 Industrial Heavy
Warranties	10 Year Residential Warranty / 5 Year Commercial Warranty
Environmental	100% Recyclable, Low VOC
Installation	Random Repeat, Reverse Sheet for Seaming Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- **Rubber Migration:** Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.