

# Commercial Vinyl Ambient


## Specifications:




Slip  
resistant




Thermal  
resistance



Dimensional  
stability



Light  
fastness



Stocked in  
New Zealand



15  
year guarantee

Level of use -	23 - 33 - 42
Total thickness -	2.50 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	PU Laquer
Total weight -	2600 g/m <sup>2</sup>
Width -	2 m
Standard length -	25 m
Inflammability -	Bfl-S1
Critical Radiant Flux -	8.1kW/m <sup>2</sup>
Slip resistance -	DS
Slip restraint -	R10
Residual indentation -	≤ 0.10 mm
Dimensional stability -	≤ 0.40 %
Light fastness -	≥ 6 degrees
Underfloor heating -	Suitable
Warranty -	15 years

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international  
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz  
59 Halwyn Drive, PO Box 914, Christchurch 8140, New Zealand  
robertmalcolm.co.nz



robert malcolm