

MANUKA

PRODUCT SPECIFICATIONS:

PILE CONTENT:	100% Solution Dyed Nylon – ECONYL [®]	
STYLE:	Twist	
PILE WEIGHT:	52oz	
PILE HEIGHT:	12mm	
CARPET THICKNESS:	14mm	
MACHINE GAUGE:	1/10"	
STITCH RATE:	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.	
WIDTH:	3.66 metres	
GRADING:	Residential Extra Heavy Duty & Stairs – 6 Stars ACCS Contract Medium Duty & Stairs – 2 Stars ACCS	
ENVIRONMENTAL ACCREDITATION:	Achieves Level 3 Certification under the ACCS Environmental Classification Scheme.	
VOC EMISSIONS:	Meets ACCS Environmental Classification Criteria	
WARRANTIES:	15 Year Limited Residential Wear Warranty 15 Year Limited Residential Stain Resistance 15 Year Limited Residential Colourfastness Lifetime Insect Resistance Lifetime Anti-Static	
COLOURS:	8847/05 Tea Tree 8847/23 Nectar 8847/45 Aromatic 8847/56 Pollination 8847/59 Spiritual	8847/21 Myrtle 8847/27 Honeycomb 8847/47 Beehive 8847/57 Ocean 8847/73 Botanical
TOLERANCE:	Manufactured to A.S. 1385 tolerances.	
INSTALLATION:	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).	
SHADING: (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault. Further information can be obtained from the Carpet Institute of Australia.	
COLOUR VARIATION:	Colour variation may occur between sample and production due to dye lot tolerances.	
MATERIAL VARIATION:	Product specifications may change without notice due to raw material availability.	
COUNTRY OF MANUFACTURE:	Australia	